

DM860B

MCP Blue, Manual Fire Alarm

General

The DM860B is a BLUE, type-B, dual action manual call point for surface mount applications.

Construction

The rugged aluminum housing, combined with a fade resistant coating, guarantees a long lasting high quality product. The revolving door, with an opening angle of 180°, contains an interchangeable break glass. The revolving door also contains a special clip that features as a failsafe to prevent the door from being closed while the unit is still triggered.

Dual action

The DM860B is defined as a type-B, dual action manual call point due to the fact that two actions are required to trigger the manual call point. First the break glass must be broken, and secondly the button must be pushed.



Standard Features

- Robust aluminium housing
- Type B / Dual action
- Surface mount

DM860B

MCP Blue, Manual Fire Alarm

Specifications

Physical

Physical dimensions	125 x 125 x 34 mm (W x H x D)
Net weight	400 g
Colour	Red

Environmental

Operating temperature	-20 to +60°C
Environment	Indoor
IP rating	IP43

Series resistor

1000 ohm or user defined

Housing

Aluminum

Dimensions

125 x 125 x 34 mm

Weight

400g

Colour

Red

Operating Temperature

-20°C to +60°C

IP Rating

IP43

Ordering Information

Part No.	Description
DM860B	MCP Blue, Manual Fire Alarm
DM800KEY	Key For DM860 And DM950 Series MCPs
DM966	Replacement Clear Windows For Push-Button-Activated Manual Call Points