

ADC-T2000

SPECIFICATIONS

POWER

4 AA Batteries or 24 V power

DIMENSIONS

4 X 4.75 X 1" (10.2 x 12.1 x 2.5cm)

OPERATING TEMPERATURE RANGE

32 to 122°F (0°C to 50°C)

SETPOINT ACCURACY

+/- 1.5°F (0.8°C)

COMMUNICATION

Z-Wave Plus

COMPATIBLE SYSTEMS

HUMIDIFIER

Yes

DEHUMIDIFIER

Yes

HEAT (FOSSIL OR ELECTRIC)

Up to 3 stages

COOL

Up to 2 stages

HEAT PUMP WITH AUX

Up to 5 stages

AUX HEAT

Up to 3 stages

DUAL FUEL (FOSSIL AUX HEAT)

Yes

FORCED AIR ZONED HEAT

Up to 3 stages

FORCED AIR ZONED COOL

Up to 2 stages



Smart Thermostat

Stay comfortable and save money with our ENERGY STAR® certified Smart Thermostat. Energy-saving schedules and an easy-to-use mobile app make it simple to remotely control your connected thermostat from anywhere. Enjoy precision comfort when paired with an Alarm.com Temperature Sensor.

INCLUDED IN THE BOX

- Thermostat
- User guide
- Batteries (x4 AA)
- Drywall anchors and screws (x3)
- Wire labels

FEATURES

- Remote access and control
- Smart scheduling
- Temperature alerts
- Geo-services automation
- Humidity Control

SMART CONFIGURATION

Complete your installation quickly by configuring the thermostat locally or from the MobileTech configuration wizard. Both options provide a fast and accurate installation experience.

BROAD HVAC COMPATIBILITY

Works with almost any heating and cooling system, including up to 3 stages of heat and two stages of cooling, multiple zones, heat pumps, and dual fuel systems.

FLEXIBLE POWER OPTIONS

Unlike most thermostats, the Alarm.com Smart Thermostat can operate on AA batteries for up to 18 months or can be connected directly to a common wire.

REMOTE SUPPORT

All device settings can be monitored and adjusted through Alarm.com's Partner Portal for instant and easy remote support, reducing maintenance costs.