

# ACU-220

## ABAX 2 WIRELESS SYSTEM CONTROLLER

**ACU-220** uses the 868 MHz radio band, in which 4 channels have been allocated. Communication between components of the **ABAX 2** system is encrypted (AES standard) and two-way, all transmissions being acknowledged. The controller works together with the **INTEGRA**, **INTEGRA Plus** and **VERSA** control panels (connection via communication bus), making expansion of the alarm system possible by adding wireless devices. It can also interact with any other alarm control panel, automation controller (when using programmable zones and outputs of the module), or work in stand-alone mode.

**ACU-220** meets the high EN 50131 requirements for Grade 2.

An advantage of the controller is its excellent transmission range, which can be up to 2000 m in the open area, depending on the device working with the controller and their operating conditions. Such good communication parameters are obtained thanks to the use of a modern radio system and antenna diversity. Depending on the level of received radio signal, **ACU-220** automatically selects the optimal antenna to be used to receive the transmission.

The system settings are configured in the ABAX 2 Soft program, which is installed on the computer and has also extensive diagnostic capabilities. When working with the **INTEGRA**, **INTEGRA Plus** and **VERSA** control panels, the **DLOADX** program or a keypad are used for the configuration. The settings can be changed and the firmware of enrolled wireless devices can be updated by radio, without having to demount them.

- compliance with the EN 50131 Grade 2 requirements
- two-way radio communication in the 868 MHz band – 4 channels
- range up to 2000 m in the open area
- support for up to 48 wireless devices
- support for wireless keypads: **INT-KWRL2** – up to 4, **VERSA-KWRL2** – up to 6
- support for up to 256 **APT-200** wireless keyfobs
- works together with the **INTEGRA**, **INTEGRA Plus** and **VERSA** control panels – connection to the communication bus
- option of autonomous operation or with any alarm control panel / controller
  - 8 programmable outputs
  - 4 programmable zones
- 4 outputs indicating the state of controller and connected wireless devices
- antenna diversity – automatic selection of the antenna that will be used to receive the transmission, depending on the level of received signal
- programming controller settings via:
  - service menu of the control panel or **DLOADX** program – when working with the **INTEGRA**, **INTEGRA Plus** or **VERSA** control panels
  - **ABAX 2 Soft** program – when the controller is working as a universal module of wireless devices (in stand-alone mode or with any control panel/controller)
- firmware update without demounting of the controller
- remote configuration and updating of devices registered to the controller
- tamper protection
- power supply: 12 V DC



**TECHNISCHE DATEN**

Spannungsversorgung ( $\pm 15\%$ )	12 V DC
Abmessungen des Gehäuses	126 x 158 x 32 mm
Abmessungen der Elektronikplatine	103 x 139 mm
Betriebstemperatur	-10°C...+55°C
Ruhestromaufnahme	75 mA
Max. Stromaufnahme	100 mA
Gewicht	222 g
Max. Luftfeuchtigkeit	93 $\pm$ 3%
Betriebsfrequenzband	868,0 - 868,6 MHz
Funkreichweite (im freien Gelände)	bis zu 2000 m
Umweltklasse gem. EN50130-5	II
Erfüllte Normen	EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-3, EN 50131-5-3
Sicherheitsgrad gem. EN 50131-3	Grade 2
Ausgänge des Typs OC	50 mA / 12 V DC