



DT2063N

Wärmemelder, 2LEDs, 2000er Serie

General

The DT2063N is a 2000 series protocol, addressable heat detector certified to class A2R. It provides good looks as well as top features, including a rate-of-rise algorithm that allows the device to raise the alarm before the fixed temperature trigger point is reached. Dual fire LEDs indicate an alarm visible from all directions, eliminating the need for special detector orientation on installation, whilst a remote indicator output is provided as standard on every device.

Installation friendly

The DT2063N is individually identified by setting an address through two rotary switches. The address is a straight numerical value and does not require binary or hexadecimal conversions, significantly reducing the risk of incorrect addressing.

All 2000 series detectors are compatible with a standard base that makes them easily interchangeable.

State of the art communication

Panel to device communication is provided through a powerful SIA protocol featuring multiple bus cycle codes and CRC error checking and ensuring reliable communications between the device and the control panel.

This enhanced protocol ensures the overall integrity and error free operation of the full system, without compromising speed.

Extended applications

For varied applications the fixed temperature trigger level of the DT2063N may be set from the CIE to accommodate higher activation temperatures.

A comprehensive line of complimentary devices completes the 2000 series portfolio:

- common use detector bases
- optical, temperature and multi-sensors
- standalone and base isolators
- sounder circuit controllers
- conventional zone monitoring units
- various supervised and non-supervised I/O units
- a comprehensive line of manual call points
- loop powered notification devices and beam detectors



Details

- Dual thermistors
- Remote signaling capabilities
- Easy numeric addressing (1-128)
- Enhanced communication protocol
- Full diagnostic self testing
- Full range including optical and multi sensors
- Full range of I/O units and accessories
- Optional isolator base
- EN54:5 approved and CPR certified

DT2063N

Wärmemelder, 2LEDs, 2000er Serie

Technical specifications

Allgemein

Statusanzeige	Dual red alarm LED
Benutzeroberfläche	LEDs
Kompatibilität	Aritech 2000 series systems
Alarmstufen	5
Konnektivität	2000 Series bases

Elektrische Angaben

Betriebsspannung	17 to 28 VDC
Aktueller Verbrauch	<270 µA (quiescent at 24 VDC) 4.7 mA (alarm at 24 VDC)

Erkennung

Detektionsprinzip	Heat
Monitoring	Alarm threshold
Empfindlichkeit	Configurable
Überwachungsbereich	<80 m ²
Luftgeschwindigkeit	Unaffected
Alarm-Temperatur	> +40°C
Rate-of-rise	Class A2

Ausgang

Ausgabemenge	1
Ausgabetyt und -Klasse	Remote indicator
Programmierbar	No
Remote Alarmausgang	4.7 mA

Physikalische Angaben

Abmessungen	100 x 50 mm (Ø x H)
Nettogewicht	83 g
Farbe	Wolkenweiß (RAL 9001)
Befestigungsart	Deckenmontage
Material	Kunststoff

Umweltbedingungen

Vandalismussicher	Nein
Betriebstemperatur	-10 to +60°C
Lagertemperatur	-10 to +70°C
Umgebungstemperatur	+25°C
Relative Luftfeuchtigkeit	10 to 95% noncondensing
Umgebung	Innen
IP Klassifizierung	IP20

Regulatory

Kompatibilität	CE, REACH, RoHS 3, WEEE
Zertifizierung	CPR
Standards	EN54-5



Als innovatives Unternehmen behält sich Carrier Fire & Security das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.