

## VTO6210B/BW IP Villa Outdoor Station





| Technical Specification |   |
|-------------------------|---|
| Model                   | VTO6210B/BW   |
| System                  |   |
| Main Processor          | Embedded Micro Processor  |
| Operation System        | Embedded LINUX OS   |
| Video                   |   |
| Video Compression       | H.264   |
| Image Sensor            | 1/4" 1MP CMOS   |
| Lens                    | 3.6mm   |
| Angle of View           | D:70° H:60°   |
| Day/Night               | Color Image   |
| Audio                   |   |
| Audio Compression       | G.711   |
| Audio Input             | Omnidirectional Mic   |
| Audio Output            | Built-in Speaker  |
| Bidirectional Talk      | Support Dual-way Bidirectional talk                               |
| Operation Mode          |   |
| Keypad                  | Single Touch Button   |
| Reader                  | Mifare Card   |
| Interface               |   |
| Door Control            | 2(1 relay out for main lock, 1 extended by access control module) |
| Alarm In                | 2(1ch unlock button, 1ch feedback)                                |
| RS485                   | 1   |
| Network                 |   |
|                         |   |

10M/100Mbps Self-adaptive

Ethernet

Features

- HD CMOS camera
- · Tempered glass panel, IP65
- · Night vision & Voice indication
- · Video & Audio messaging
- $\cdot$  Remote intercom with mobile APP
- $\cdot$  Surface mounted



| Network Protocol    | TCP/IP                 |
|---------------------|------------------------|
| General             |                        |
| Ingress Protection  | IP65                   |
| Tamper Switch       | 1                      |
| Installation        | Surface                |
| Material            | Tempered Glass         |
| Power               | DC 12V                 |
| Power Consumption   | Standby ≤1W, Work ≤10W |
| Working Temperature | -30°C~+60°C            |
| Relative Humidity   | 10%~90%RH              |
| Dimensions          | 154.2mm×114.2mm×43.0mm |
| Weight              | 0.6Kg                  |

## Dimensions View Area

## Application





Rev 001.001 © 2016 Dahua . All rights reserved. Design and specifications are subject to change without notice