

IP VIDEO DOORPHONE KIT FOR OUTDOORS + 7" IP TOUCHSCREEN.



KEY FEATURES

- IP video doorphone kit for outdoors + 7" IP touchscreen

- Video doorphone station
- IP video doorphone station for small houses with 1 call button
- Linux OS
- IP colorful IP camera, 1,3 MP
- Resolution: 720P (1280x720) at 25 fps
- Autoadaptive IR leds
- H.264
- Mifare proximity card reader
- Compatible with external readers RS-485 (HYUNDAI protocol)
- Remote unlock via client software or app mobile (console required)
- Tamper alarm supported and alarm by magnetic contact
- G.711u
- Omnidirectional and speaker incorporated
- 2 way audio with noise supression and echo cancellation
- Ethernet: 10/100Mbps auto-adaptative
- Network protocols: TCP/IP and RTSP
- Alarm: 4 in / 1 out
- Port RS485 Half-Duplex
- Metal case
- IP65
- Working temperature: -40° ~ +60°C
- Working RH 10% ~ 90%
- Power supply: 12V DC
- Power supply by network cable up to 40 meters (HYU-560 is required)
- Consumption: <12W
- Dimensions: 182 x 100 x 33 mm
- IP color monitor
- 7" IP indoor monitor with capacitive color touchscreen
- Resolution: 800 x 480
- H.264 compression
- 4 mechanical buttons
- Linux OS
- Audiovisual communication with hands-free between the monitor and the video door station
- G.711u audio compression
- Omnidirectional microphone and speaker incorporated
- Noise supression and echo cancellation
- Video doorphone and external cameras supervision supported
- Remote unlock via app
- Integrated high performance SOC processor
- 2 alarm input channel supported

RELATED PRODUCTS



HYU-560