

# HYU-501N

HYU-501N

HYUNDAI

## HYUNDAI Multifunction 5-in-1 CCTV Tester

HYUNDAI ONVIF HDCVI™ HDTVI AHD CVBS

- 5-in-1 multifunctional CCTV monitor with 7" retina touch screen with CVI/TVI/AHD cameras image testing up to 4K/8MP
- Incorporates dual-band WiFi (creates access point)
- Audio input/output
- PTZ control
- UTP test
- PoE output
- 24V power output
- Onvif support
- HDMI 4K input/output
- 12V DC.



### Reference / Model

HYU-501N / HYU-501N

5-in-1 Multifunctional CCTV Tester (CVBS, CVI, TVI, AHD, IP)

7" retina touch screen (1920x1200 pixels)

Supports 4K and H.265/H.264 decoding with a display of the mainstream

Supports 4K/8MP in CVI and 5 MP in AHD and TVI

HDMI input supports 4K resolution (30 fps)

HDMI output supports up to 4K (3840x2160)

Dual IP/analog test (simultaneous analog and IP camera test)

Drop-down menu, shortcut-accessible menu

Built-in WiFi: Allows receiving images from WiFi cameras and supports WiFi hotspot creation.

Image testing of CVI/TVI/AHD cameras up to 4K/8MP

BNC attenuation test

AHD/CVI/TVI camera test supports image capture, video recording, and playback, and 4X zoom.

CVBS loop test: Transmit or receive an analogue video signal

**HYUNDAI Multifunction 5-in-1 CCTV Tester**

<b>Reference / Model</b>	<b>HYU-501N / HYU-501N</b>
	Onvif IP camera test supports 4K resolution
	Display of analogue camera images: Automatically adapts to PAL and NTSC formats.
	Fast Onvif: One keystroke generates a test report, including IP address, resolution and decoding.
	Connection of IP cameras via RJ45 and WiFi supports 1080p
	Real-time display
	PTZ control, image captures, video recording recorded video playback
	TV output with colour bar generator
	UTP cable test: TDR 2.0 function (to locate and locate breakpoints in UTP cable), connection status, cable sequence on screen, saving of test report
	PoE voltage measurement, PING test, IP address scanning, port intermittency, etc.
	Built-in 150Mbps dual-band WiFi
	WiFi analyser
	2 RJ45 Gigabit network ports
	48V DC PoE output: Provides temporary power to PoE cameras
	24V /2A power supply output
	Audio input/output
	LED torch, calculators, players and other tools/applications
	Power supply: 12V DC /2A
	Built-in 7.4V, 7800mAh lithium-polymer battery
	Fast battery charging
	Working temperature: -10°C ~ +50°C
	Dimensions: 255 x 160 x 46 mm
	Weight: 950 g
	Anti-sunlight cover
	Apps included: EVOPLUS, HYUVMS, ASMS, HYU CONNECT, HYUPLUS