

4 in 1 BULLET CAMERA, 2MP, MOTORIZED ZOOM & POSITIONER

CVBS HDCVI™

HDTVI AHD



FEATURES

- 1080p HD resolution with Sony® CMOS sensor
- IR illumination up to 80 meters
- 2.8~12 mm varifocal lens (autofocus)
- Transmission distance up to 300 (theoretical) meters
- 4 in 1 output: CVBS, HDCVI, HDTVI, AHD
- OSD menu and lens control not compatible with NETXGEN ZVR
- BLC, Real WDR, ROI
- Positioner: 0°~250° (H), -10°~55° (V)
- Speed: 0,5°~15°/sec. (H), 0,5°~10°/sec. (V)
- 255 presets, 8 rounds, 4 patterns
- OSD menu, CVI video output
- Pelco protocol
- IP66
- Surge protection

CAMERA

Image sensor	1/2,8" Sony® CMOS, 2 MP
Effective pixels	1920(H) x 1080(V)
Frames per second	PAL/NTSC: 25/30 fps @1080P
IR illumination	4 array led. 80 meters
Minimum illumination	0 lux IR ON
Video output	AHD, HD-CVI, HD-TVI, 1 BNC CVBS

LENS

Lens	2.8 ~ 12 mm
Focus mode	Automatic

FUNCTIONS

Day/night	Auto (ICR dual)
OSD menu	Supported
Backlight compensation	BLC, Real WDR
ROI	Supported

POSITIONER & TELEMETRY

Horizontal range	0° ~ 250°
Vertical range	-10° ~ +55°
Manual speed	0,5° ~ 15°/sec. horizontal / 0,5° ~ 10°/sec. vertical
Presets	255 presets (8 rounds, 4 patterns)

ELECTRICAL & ENVIRONMENTAL

Power supply	12V DC (±10%)
Transmission distance	Up to 300 meters (theoretical) via 75-3 coaxial cable
Protection	IP66

PHYSICAL FEATURES

Dimensions	153 x 93 x 130 mm
------------	-------------------