



HDCVI™ HDTV I AHD CVBS
EMP

KEY FEATURES

- 4 in 1 dome PRO series with Smart IR of 70 m for outdoors
- 2MP CMOS
- 4 in 1 switch video output
- 2,7 ~ 13,5 mm motor lens (102°~31°)
- ICR filter
- OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment
- IP67
- 3AXIS
- 12V DC

FEATURES

- 2 MP CMOS high performance
- 1920x1080
- 4 in 1 video output
- Ultralow illumination
- WDR true 120dB, 3DDNR
- 2,7 ~ 13,5 mm motor lens with autofocus
- Smart IR: 70 m range
- IP67

SPECS

- 2 MP CMOS sensor
- Digital resolution: 1080P (1920x1080) at 25 fps
- 4 in 1 video output switch (HDCVI, HDTV I, AHD, CVBS)
- 0,005 lux F1.2 (color, AGC On) / 0 lux IR On
- Removable mechanical filter
- Smart IR: EXIR 2.0 technology, 70 meters
- 2,7 ~ 13,5 mm motor lens
- Horizontal viewing angle: 102°~31°
- Automatic focus control
- OSD via coaxial (300 m range)
- Auto/manual white balance
- Automatic Gain Control
- Backlight compensation: BLC, HLC
- WDR true 120dB
- 3DDNR
- Mirror mode supported
- Adjustment of brightness and sharpness
- Working temperature: 40°C~+60°C
- RH: 90% (without condensation)
- IP67
- Metal case
- Power supply: 12V DC (±25%)
- Consumption: 7,7W
- Dimensions: 123,87 (An) x 110,24 (Al) x 134,3 (L) mm
- Weight: 600 g
- 3AXIS: 0°~360°(PAN), 0°~75°(TILT), 0°~360°(Rotation)