



**STARLIGHT 2MP HDCVI™**  
**HDTVI AHD CVBS**

**KEY FEATURES**

- 4 in 1 dome StarLight series with IR illumination of 20~30 m for outdoors
- 1/2,8" Sony CMOS, 2MP at 1080P
- 4 in 1 video output switch
- 2,8~12 mm motor lens with autofocus
- ICR filter
- OSD, AWB, AGC, 2D/3D-DNR, BLC, digital WDR, sense up, defog, mirror, motion detection and privacy mask
- IP66
- Lightning-proof
- 3AXIS
- 12V DC

4 IN 1 DOME STARLIGHT SERIES WITH IR ILLUMINATION OF 20~30 M FOR OUTDOORS

**FEATURES**

- 2 MP Sony® CMOS
- 1080P at 25 frames per second
- Starlight technology
- 2,8 ~ 12 mm motor lens with autofocus
- OSD menu control via coaxial cable (UTC)
- AWB, AGC, BLC, 2D/3DDNR
- WDR digital, Sense Up, Defog, Mirror
- Motion detection and privacy mask
- Lightningproof
- IP66

**SPECS**

- 1/2,8" Sony® CMOS of 2 MP
- Digital resolution: 1080P (1920x1080)
- 4 in 1 video output switch (HDCVI, HDTVI, AHD, CVBS)
- 0,001 lux F1.2 (color) / 0 lux IR On
- Removable mechanical filter
- Smart IR: 18 leds array, 20~30 meters
- 2,8 ~ 12 mm motor lens with autofocus
- OSD via coaxial (only on CVI mode, 300 m range, not compatible with NEXTGEN ZVR)
- White balance: Auto, ATW, Indoor, Outdoor, Manual
- Automatic Gain Control
- BLC
- Digital WDR
- 2D/3D noise reduction
- Sense Up, mirror, defog
- Motion detection and privacy mask
- Working temperature 20°C ~ +60°C
- RH: 10% ~ 90%
- IP66
- Lightningproof
- Metal case
- Power supply: 12V DC (±10%)
- Consumption: <5W
- Dimensins: Ø119 x 98 (H) mm
- 3AXIS: Wall and ceiling installation