

IP HYUNDAI NEXTGEN IP BULLET CAMERA, 2MP WITH IR OF 30M, SUITABLE FOR OUTDOORS



KEY FEATURES

- IP HYUNDAI NEXTGEN IP bullet camera, 2MP with IR of 30m, suitable for outdoors
- H.265+/H.265/H.264+/H.264/MJPEG
- Triple stream
- 1/2,8" CMOS, 2MP
- 1080P@25 fps
- ICR filter
- 0,028 lux
- 2,8 mm lens (103°)
- OSD, AGC, BLC, HLC, WDR true 120dB, 3D-DNR, 1 fixed ROI
- IVS

FEATURES

- 1/2,8" CMOS sensor, 2 MP
- 1080P at 25 fps
- 2,8 mm lens
- H.265+, H.265, H.264+, H.264
- Triple stream
- WDR 120dB, BLC, HLC, 3DDNR, ROI
- 2 analysis behaviour and face detection
- IR illumination up to 30 meters
- MicroSD card slot up to 128GB (card is not included)
- IP67
- PoE supported

SPECS

- 1/2,8" CMOS sensor, 2 MP
- Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720), etc.
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 1080P, 1,3MP, 720P (25 fps)
- Stream 2: 640x480, 640x360, 320x240 (25 fps)
- Stream 3: 1080P, 720P, 640x360, 352x288 (25 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 30 meters
- Minimum illumination: 0,028 lux F2.0 color (AGC On)
- 2,8 mm lens
- Viewing angle: 103°(H), 59°(V), 118°(D)
- OSD menu
- AGC
- BLC, HLC
- WDR true 120dB
- 3D digital noise reduction
- 1 fixed ROI stream 1 and stream 2
- Adjust rotation, brightness, saturation, contrast, sharpness and white balance through client software and web browser
- Intelligent functions: Tripwire, intrusion detection
- Facial detection
- Reset button
- MicroSD/SDHC/SDXC card slot up to 128GB (card is not included)
- Network interface: RJ45 (10/100M)
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug&Play connection with NVR NEXTGEN
- Compatible with DDNS DEMES
- Power supply: 12V DC