

HYUNDAI NEXTGEN IP BULLET CAMERA, 2 MP WITH IR OF 50M,  
VANDAL PROTECTION FOR OUTDOORS H.265+/ H.265/ H.264+/  
H.264/MJPEG



## KEY FEATURES

- HYUNDAI NEXTGEN IP bullet camera, 2 MP with IR of 50m, vandal protection for outdoors H.265+/ H.265/ H.264+/ H.264/MJPEG
- Triple stream
- 1/2,8" CMOS, 2MP
- 1080P@25 fps
- ICR filter
- 0,018 lux
- 2,8~12 mm motor lens with autofocus (110°~31°)
- OSD, AGC, BLC, HLC, WDR true 120dB, 3D-DNR, 1 fixed ROI
- IVS
- Face detection
- 2 way audio
- Alarm: 1 in / 1 out
- BNC video output
- Reset button
- MicroSD
- Onvif, ISAPI
- IP66, IK10
- 3AXIS
- 12V DC
- PoE+



## FEATURES

- 1/2,8" CMOS sensor, 2 MP
- 1080P at 25 fps
- 2,8 ~ 12 mm motorlens with autofocus
- H.265+, H.265, H.264+, H.264
- Triple stream
- WDR 120dB, BLC, HLC, 3DDNR, ROI
- 2 behaviour analysis and face detection
- IR illumination up to 50 meters
- MicroSD card slot up to 128GB (card is not included)
- IP66
- IK10
- PoE+ supported

## SPECS

- 1/2,8" CMOS sensor, 2MP
- Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720), etc.
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 1080P, 1,3MP, 720P (25 fps)
- Stream 2: 640x480, 640x360, 320x240 (25 fps)
- Stream 3: 1080P, 720P, 640x360, 352x288 (25 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 50 meters
- Minimum illumination: 0,018 lux F2.0 color (AGC On)
- 2,8 ~ 12 mm motor lens
- Automatic focus control
- Viewing angle: 110°~31°(H), 58°~18°(V), 136°~36°(D)
- OSD menu
- AGC
- BLC, HLC
- WDR true 120dB
- 3D digital noise reduction
- 1 fixed ROI stream 1 and stream 2
- Adjust rotation, brightness, saturation, contrast, sharpness and white balance through client software and web browser
- Intelligent functions: Tripwire detection, intrusion detection
- Face detection
- BNC video output (only for adjustments)
- Audio: 1 in / 1 out
- Alarm: 1 in / 1 out
- Reset button
- MicroSD/SDHC/SDXC card slot up to 128GB (card is not included)
- Network interface: RJ45 (10/100M)

- Network protocol: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug&Play connection with NVR NEXTGEN
- Compatible with DDNS DEMES
- Power supply: 12V DC
- Consumption: 1,2A, max. 14,5W
- PoE+ 802.3at supported, class 4
- Working temperature 30°C ~ +60°C
- RH: 95% (without condensation)
- IP66
- IK10
- Metal case
- Dimensions: Ø144,13 x 332,73 (L) mm
- Weight: 1,7 kg
- 3AXIS: 0°~360°(PAN), 0°~90°(TILT), 0°~360°(Rotation)
- Power supply is not included