



**KEY FEATURES**

- HYUNDAI IP fixed dome with 20 m Smart IR for outdoors
- H.265 / H.264 format
- 1/2.7" CMOS of 5 MP
- Resolution of up to 5MP @ 10 fps
- Triple Stream 3.6 mm lens
- ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks
- Audio: 1 input / 1 output
- Onvif
- IP67 12V DC PoE Reset button

**HYU-751** HYU-751

HYUNDAI IP FIXED DOME WITH 20 M SMART IR FOR OUTDOORS

**FEATURES**

- 1/2.7" CMOS sensor 5 MP
- H.265 and H.264 encoding with triple stream
- 5MP (2592x1944) at 10 fps, 3MP (2048x1536) at 25 fps
- Digital WDR, day/night with ICR filter, 2D / 3DDNR, AWB, AGC, 4 ROI
- 3.6 mm lens
- Smart IR up to 20 meters
- IP67
- SD slot
- Supports PoE

**SPECS**

- 1/2.7" CMOS sensor, 5MP
- H.265 / H.264 compression formats
- Triple stream
- Digital resolution: 5MP (2592x1944), 3MP (2048x1536), 1080P (1920x1080), D1 (720x576), VGA (640x480)
- Stream 1: 5MP (10 fps), 3MP (25 fps)
- Stream 2: D1, VGA (25 fps)
- Stream 3: D1, VGA (25 fps)
- Supports constant and variable bit rate (CBR / VBR)
- Day / night mode with removable mechanical filter
- Smart IR: 18 SMD LEDs, 20 meters
- 0.06 lux F1.2 (color) / 0.08 lux F1.2 (B/W) / 0 lux IR On
- 3.6 mm lens
- OSD overlay
- Auto white balance
- Automatic gain control
- Automatic exposure control
- Digital WDR
- 2D / 3DDNR digital noise reduction
- 4 ROI zones
- Motion detection and privacy mask
- Adjust brightness, contrast, saturation, sharpness and image rotation (normal, 90°, 270° and automatic)
- Intelligent detection: Occlusion detection, blur detection, brightness detection, color detection, sound detection, abandon detection, motion detection, virtual cord, regional invasion
- Audio: 1 in / 1 out
- SD card slot (not included)
- Network interface: RJ45 (10 / 100M) autoadaptable
- Network protocols: IPv4, IPv6, HTTP, HTTPS, 802.1x, TCP / IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP,
- DHCP, DNS, PPPOE, DDNS, FTP
- Onvif compatible
- Supports cloud service