

IP BULLET CAMERA WITH IR ILLUMINATION OF 30M, FOR OUTDOORS, 4 MP



PerformanceLine  



KEY FEATURES

- IP bullet camera with IR illumination of 30m, for outdoors, 4 MP
- Formato H.265+/H.265/H.264/H.264+/MJPEG
- 1/3" CMOS, 4MP
- Digital resolution: 4MP, 1080P, 720P, 20FPS
- Mechanical filter
- 0,01 lux
- 2,8 mm fixed lens (100°)
- OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI
- IP67
- 3AXIS bracket

FEATURES

- 1/3" CMOS sensor, 4 MP
- Digital resolution: 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), etc.
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 4MP, 1080P, 720P (20 fps)
- Stream 2: D1, CIF, VGA, QVGA (20 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 30 meters
- Minimum illumination: 0,01 lux F1.2 color / 0 lux IR On
- 2,8 mm fixed lens (100°)
- OSD menu, AGC, BLC, digital WDR, 3DDNR
- 1 fixed ROI stream 1 and stream 2
- Motion detection and privacy mask
- Bright adjustment, saturation, contrast, sharpness, mirror
- Network interface: RJ45 (10/100 BaseT)
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6 UDP, Bonjour
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug&Play with NVR NEXTGEN
- Compatible with DDNS DEMES
- Power supply: 12V DC /5W (Max 7W PoE)
- PoE 802.3af supported
- Working temperature: 30°C ~ +50°C
- RH: 95%
- IP67
- Lightningproof 2KV
- PVC and metal case
- Dimensions: Ø70 x 172,7 mm
- Weight: 280 g
- 3AXIS bracket
- Power supply is not included