

PTZ-H2EN20 | 2MP 20x Full HD HDCVI IR PTZ Dome Camera


- 20x optical zoom
- Max. 25/30fps@1080P(1920x1080) & 50/60fps@720P resolution
- DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus
- Control over coaxial cable, long distance real-time transmission
- HD and SD switchable
- Max 240°/s pan speed, 360° endless pan rotation
- Up to 300 presets, 5 auto scan, 8 tour, 5 pattern
- Built-in 2/1 alarm in/out
- Support intelligent 3D positioning with DH-SD protocol
- IR Distance up to 100m
- IP66, OSD


Technical Specifications

Camera	
Image Sensor	1/2.8" Exmor CMOS
Effective Pixels	1920(H) x 1080(V), 2Megapixels
Scanning System	Progressive
Electronic Shutter Speed	1/1 ~ 1/30,000s
Minimum Illumination	Color: 0.05Lux@F1.4; B/W: 0.005Lux@F1.4; 0Lux (IR on)
S/N Ratio	More than 50dB
Resolution	25/30fps@1080P, 25/30/50/60fps@720P
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)
Camera Features	
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR (Digital WDR)
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Gain Control	Auto / Manual
Noise Reduction	2D/3D
Privacy Masking	Up to 24 areas
Digital Zoom	16x
Lens	
Focal Length	4.7mm~94mm (20x Optical zoom)
Max. Aperture	F1.4 ~ F2.6
Focus Control	Auto / Manual
FOV-H	H: 54.1°~ 3.1°
Close Focus Distance	100mm~ 1000mm

Pan/Tilt/Rotation	
Pan/Tilt Range	Pan: 0° ~ 360° endless Tilt: -15° ~ 90° auto flip 180°
Manual Control Speed	Pan: 0.1° ~ 160° /s; Tilt: 0.1° ~ 120° /s
Preset Speed	Pan: 240° /s; Tilt: 200° /s
Presets	300
PTZ Mode	5 Pattern, 8 Tour, Auto Pan, Auto Scan
Speed Setup	Human-oriented focal length/ speed adaptation
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period
Protocol	DH-SD, Pelco-P/D (Auto recognition)
IR Distance	100m (2 near IR LED+ 4 far IR LED)
Audio	
Interface	1 channel In
Auxiliary Interface	
RS485	1
Alarm	2/1 channel In/Out
General	
Power Supply	AC 24V/3A (± 10%)
Power Consumption	10.5W, 26W (IR on, Heater on)
Working Environment	-40°C ~ 60°C / Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	N/A
Dimensions	Φ204.7(mm) x 359.9(mm)
Weight	7.5kg

PTZ-H2EN20 | 2MP 20x Full HD HDCVI IR PTZ Dome Camera

Dimensions (mm)



Accessories (included)

Wall Mount:
OS-64FB



Power Supply:
AC24V/3A



Accessories (optional)

Mount adapter:
OS-PFA111



Ceiling Mount:
OS-PFA112



Ceiling Mount:
OS-PFA113



Ceiling Mount:
OS-PFB300C



Junction Box:
OS-PFA120



Pole Mount:
OS-PFA150



Corner Mount:
OS-PFA151

