

AS620RF-RC

Remote control for AS620RF-TR-N, 868 Mhz

The AS620RF-RC is a two-way remote control with four programmable buttons to send easy remote commands to the transceiver module AS620RF-TR-N. Immediate visual feedback of the status will be provided by the 4 status LEDs, one for each output.

All the main functions of an alarm control panel can be assigned to the buttons, i.e. switching on, switching off, specific output activations, etc.

Up to 4 remote controls can be added to allow the end-user to operate his security system in a quick and easy way.



Einzelheiten

- Remote control for AS620-TR-N
- Two-way wireless communication
- Supplied with two different button graphics
- Up to 4 remote controls with single AS620RF-TR-N
- Status LEDs

AS620RF-RC

Remote control for AS620RF-TR-N, 868 Mhz

Technische Spezifikationen

Elektrische Angaben

Betriebsspannung	3 VDC lithium battery, model CR2032
------------------	-------------------------------------

Physikalisch

Abmessungen	80 x 35 x 16 mm
-------------	-----------------

General

Operating frequency	868 MHz
---------------------	---------

Wireless signal range	200 m
-----------------------	-------

Compatability	AS620RF-TR-N
---------------	--------------



Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.