

IPMECD-0262-M4560

Barrier Rod



- 4.5 to 6 m telescopic arm that can be used on either side of the boom gate.
- Made of aluminum alloy, and designed with an anti-rust case that was treated with electrostatic spray.
- The main pole has an elastic anti-smashing rubber strip at the bottom, while the auxiliary pole does not.

Series Overview

Constructed from highly durable aluminum alloy, the Barrier Rod features an advanced anti-rust coating on its surface. Additionally, it is equipped with an elastic anti-collision rubber strip at the bottom for added protection.

Technical Specification

Basic

Color	Red and white
Matched Product	DHI-IPMECD-2062 Series Barrier

General

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Humidity	10%–90% (RH), non-condensing
Casing Material	Metal (Aluminum)
Product Dimensions	3,700.0 mm × 115.0 mm × 45.0 mm (145.67" × 4.53" × 1.77") (L × W × H)
Packaging Dimensions	3,800.0 mm × 150.0 mm × 100.0 mm (149.61" × 5.91" × 3.94") (L × W × H)
Net Weight	6.7 kg (14.77 lb)
Gross Weight	7.1 kg (15.65 lb)
Installation	Compatible with barrier installation
Anti-corrosion Level	Basic Protection

Ordering Information

Type	Model	Description
Barrier Rod	IPMECD-0262-M4560	Barrier Rod

Dimensions (mm[inch])

