

DH-SDT4E425-8P-GB-APV1

8+4MP 25x TiOC Network Panoramic PTZ Camera



 Xinghan X-Spans

- Overview channel: Outputs 180° wide angle splicing image
- Detail channel: 1/2.8"4Megapixel CMOS
- 25x optical zoom
- Max. 25/30 fps@8M
- IR distance up to 100 m
- Smart tracking
- Perimeter protection
- Active deterrence
- Smart dual light +

System Overview

Designed with more lens than the conventional PTZ camera, the X-Spans series camera captures an expansive view, producing wide, vivid images. It has the combined power of the panoramic and detail camera in its structure and is highly cost-effective, greatly reducing the installation cost of security systems. It also leverages its two cameras to perform smart tracking, and has an independent mode that allows you to separately use each camera.

Functions

Starlight Technology

For challenging low-light conditions, Dahua's Starlight Ultra-low Light Technology has exceptional light sensitivity, capturing images in vivid detail, even in lighting as low as 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, producing clear images in dark environments.

Smart Codec

With advanced scene-adaptive rate control algorithm, Dahua smart codec technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, and more, and uses secondary recognition during target detection to improve alarm accuracy.

Acupick

This industry-leading search technology effectively utilizes both front-end and back-end intelligence to help with searching through massive video data to quickly and conveniently locate targets with greater precision.



Xinghan Large-Scale AI Models-Vision

Xinghan Large-Scale AI Models-Vision seamlessly expands the storage and operational capacity of algorithmic models through the powerful integration of edge AI model algorithms and NPU computing power. Engineered with a lightweight transformer architecture and enhanced by model distillation and quantization techniques, it optimizes the computing power consumption of ViT operators. This enables the system to collaborate on multiple tasks simultaneously through joint inference between small and large models optimized for edge devices.

Smart Tracking

The panoramic camera links with the detail camera to track targets. When the target enters the panoramic area, the detail camera starts to monitor them and tracks their movement by rotating, zooming and focusing the PTZ camera lens. This allows the camera to produce highly detailed images with the movement of targets for security personnel.

Smart Dual Light

Dahua Smart Dual Light technology adopts smart algorithm to detect targets. Usually, the IR illuminator is on at night; when the target appears in the monitoring area, the white light is on, and the camera records the full-color video and information of key events. That is, the camera links snapshot and video with full-color image. When the target is out of the monitoring area, the white light is off and the IR illuminator is on, which reduces light pollution efficiently.

Protection (IP66, TVS 6000 V)

IP66, TVS 6000 V lightning proof, surge protection, and voltage transient protection.

Technical Specification

Camera

| | |
|-----------------------------------|--|
| Image Sensor | Overview channel: 1/2.7" CMOS; Detail channel: 1/2.8" CMOS |
| Pixel | Overview channel: 8 MP; Detail channel: 4 MP |
| Max. Resolution | Overview channel: 4096 (H) × 1860 (V); Detail channel: 2560 (H) × 1440 (V) |
| ROM | Overview channel: 4 GB; Detail channel: 4 GB |
| RAM | Overview channel: 2 GB; Detail channel: 1 GB |
| Electronic Shutter Speed | 1 s–1/30,000 s |
| Scanning System | Progressive |
| Min. Illumination | Overview channel: 0.005 lux@F1.4 (Color, 30 IRE); 0.0005 lux@F1.4 (B/W, 30 IRE); 0 lux (illuminator on) Detail channel: 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (illuminator on) |
| Illumination Distance | Overview channel: 30 m (98.43 ft) (IR); 30 m (98.43 ft) (white light); Detail channel: 100 m (328.08 ft) (IR); 50 m (131.23 ft) (white light) |
| Illuminator On/Off Control | Overview channel: Manual; Auto; Off Detail channel: Zoom Prio; Manual; Auto; Off |
| Illuminator Number | Overview channel: 2 (IR light); 2 (White light); Detail channel: 2 (IR light); 2 (Warm light) |

Lens

| | |
|-----------------------------|--|
| Focal Length | Overview channel: 2.8 mm; Detail channel: 5 mm–125 mm |
| Max. Aperture | Overview channel: F1.4; Detail channel: F1.6-F3.6 |
| Field of View | Overview channel: H: 180°; V: 86°; Detail channel: H: 51.9°–3.0°; V: 39.7°–2.2°; D: 63.1°–3.7° |
| Optical Zoom | Overview channel: NA; Detail channel: 25× |
| Focus Control | Auto; manual; semi-auto |
| Close Focus Distance | Overview channel: 0.6 m (1.97 ft); Detail channel: 0.1 m–0.5 m (0.33"–1.64") |
| Iris Control | Overview channel: NA; Detail channel: Auto; manual; iris prio |

| | Detect | Detect | Observe | Recognize | Identify |
|----------------------|---|-----------------------|-----------------------|----------------------|---------------------|
| DORI Distance | Overview channel: 2.8 mm | 56.0 m (183.72 ft) | 22.4 m (73.49 ft) | 11.2 m (36.74 ft) | 5.6 m (18.37 ft) |
| | Detail channel: W | 100.0 m (328.08 ft) | 40.0 m (131.23 ft) | 20.0 m (65.62 ft) | 10.0 m (32.81 ft) |
| | Detail channel: T | 2500.0 m (8202.00 ft) | 1000.0 m (3280.80 ft) | 500.0 m (1640.40 ft) | 250.0 m (820.20 ft) |
| | *DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool. | | | | |

PTZ

| | |
|-----------------------|---|
| Pan/Tilt Range | Pan: 0° to 360° endless Tilt: –15° to +90°, auto flip 180° |
|-----------------------|---|

| | |
|-----------------------------|---|
| Manual Control Speed | Pan: 0.1°/s–180°/s; Tilt: 0.1°/s–90°/s |
| Preset Speed | Pan: 0.1°/s–180°/s; Tilt: 0.1°/s–90°/s |
| Preset | 300 |
| Tour | 8 (up to 32 presets per tour) |
| Pattern | 5 |
| Scan | 5 |
| Power-off Memory | Yes |
| Idle Motion | Preset; Pattern; Tour; Scan |

Intelligence

| | |
|-----------------------------------|--|
| IVS (Perimeter Protection) | Tripwire; intrusion; crossing fence detection; loitering detection; abandoned/missing object; fast moving; parking detection; people gathering; human alarm classification; linkage tracking |
| Smart Tracking | WizTracking: Xinghan large-scale AI models-driven human & vehicle tracking. Relay tracking: X-SPANS series only. Tracking continues after target exits overview channel until target leaves scene. Linkage tracking: X-SPANS series only. Tracks only targets visible in overview channel. |
| SMD | SMD4.0 |
| Acupick | Uses deep learning algorithms and works with backend devices to accurately match targets, such as people and motor vehicles, and search through live and recorded videos to quickly locate targets (Overview channel support) |
| Auto Patrol | After an IVS alarm is triggered, it can link with up to 5 presets or scan to patrol the key areas. IVS can be enabled with SMD at the same time. |

Active Deterrence

| | |
|----------------------|---|
| Light Warning | Red-Blue light warning; Flash duration: 5 s–30 s; Flash frequency: high, medium, low |
| Sound Warning | Offers 11 sound alarm and 10 custom sound alarms can be imported. Sound can be set from 0%–100%. Play times can be set from 1-10. |

Video

| | |
|-----------------------------|---|
| Video Compression | Smart H.265+;H.265;Smart H.264+;H.264B;H.264M;H.264H;MJPEG(Sub Stream 1) |
| Streaming Capability | 3 streams |
| Resolution | Overview channel: 8M (4096 × 1860); 2M (2048 × 928); 1080p (1920 × 1080); 720p (1280 × 720); 1024 × 448; D1 (704 × 576/704 × 480);VGA (640 × 480);CIF (352 × 288/352 × 240); Detail channel: 4M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480);VGA (640 × 480); CIF (352 × 288/352 × 240) |
| Video Frame Rate | Overview channel: Main stream: 4096 × 1860 @ (1–25/30 fps) Sub stream 1: 1024 × 448/D1/VGA/CIF @ (1–25/30 fps) Sub stream 2: 2048 × 928/1080p/1.3M/720p @ (1–25/30 fps); Detail channel: Main stream: 4M/3M/1080p/1.3M/720p @ (1–25/30 fps) Sub stream 1: D1/VGA/CIF @ (1–25/30 fps) Sub stream 2: 1080p/1.3M/720p/ @ (1–25/30 fps) |

| | |
|--------------------------|--|
| Bit Rate Control | CBR/VBR |
| Video Bit Rate | Overview channel: H264: 128 kbps–16,384 kbps H265: 51 kbps–13,312 kbps; Detail channel: H264: 96 kbps–16,384 kbps H265: 38 kbps–10,240 kbps |
| Day/Night | Overview channel: Auto; Color; B/W; Electronic Detail channel: Auto; Color; B/W; Electronic |
| BLC | Yes |
| WDR | Overview channel: DWDR; Detail channel: 120 dB |
| HLC | Yes |
| White Balance | Overview channel: Auto; indoor; outdoor; tracking; manual; sodium lamp; natural light; street lamp Detail channel: Auto; indoor; outdoor; tracking; manual; sodium lamp; natural light; street lamp |
| Gain Control | Overview channel: Auto; manual; gain prio Detail channel: Auto; manual; gain prio |
| Noise Reduction | Overview channel: 2D NR; 3D NR Detail channel: Auto: 2D NR; 3D NR |
| Motion Detection | Yes |
| Region of Interest (RoI) | Yes |
| Image Stabilization | Overview channel: NA Detail channel: Electronic Image Stabilization (EIS) |
| Defog | Overview channel: Electronic Detail channel: Electronic |
| Digital Zoom | Overview channel: NA; Detail channel: 16x |
| Image Rotation | Overview channel: NA Detail channel: 180 |
| S/N Ratio | Overview channel: ≥55 dB Detail channel: ≥55 dB |
| Privacy Masking | Up to 24 areas can be set, with up to 8 areas in the same view Multiple colors and mosaic available |

Audio

| | |
|-------------------|---|
| Audio Compression | PCM, G.711A, G.711Mu, G.726, MPEG2-Layer2, G.722.1, G.729 |
|-------------------|---|

Network

| | |
|---------------------|--|
| Network Port | RJ-45 (100/1,000 Base-T) |
| Network Protocol | HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; IPv6; 802.1x; SSL; QoS; FTP; UPnP; ICMP; SNMP; IGMP; ARP; RTCP; RTP; PPPoE; RTMP; Bonjour; NFS |
| Interoperability | ONVIF (Profile S & Profile G & Profile T);CGI;SDK;P2P |
| Streaming Method | Unicast/Multicast |
| User/Host | 20 (total bandwidth: 64 M) |
| Storage | Micro SD card (512 GB); FTP/SFTP; NAS |
| Browser | web5.0: IE 9 and later versions; Chrome 41 and later versions; Firefox 52 and later versions; Safari 10 and later versions |
| Management Software | DMSS; DSS Pro |
| Mobile Client | iOS; Android |

Certification

| | |
|----------------|--|
| Certifications | CE: EN 50130-4 EN 55032 EN 55035 EN 61000-3-3 EN IEC 61000-3-2 EN 62368-1 |
|----------------|--|

Port

| | |
|---------------|---|
| Audio Input | 1 channel (LINE IN, bare wire) |
| Audio Output | 1 channel (LINE OUT, bare wire; built-in speaker (mutually exclusive)) |
| Alarm Input | 2 (on-off value input: 0–5 VDC) |
| Alarm Output | 1 channel |
| Alarm Linkage | Capture; recording; send email; preset; tour; pattern; alarm digital output; audio; warning light |
| Alarm Event | Motion/tampering detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection |

Power

| | |
|-------------------|---|
| Power Supply | 12 VDC, 3 A ± 10%; PoE (802.3at) |
| Power Consumption | Basic: 14 W; Max: 25 W (illuminator + heating glass + Siren and Light Active Deterrence + ICR + PTZ) |
| Power Adapter | Optional |

Environment






| | |
|-----------------------|--|
| Operating Temperature | –40 °C to +65 °C (–40 °F to +149 °F) |
| Operating Humidity | ≤95% |
| Protection | IP66; TVS 6000 V lightning proof; surge protection; voltage transient protection |

Structure

| | |
|--------------------|---|
| Product Dimensions | 194.2 mm × 160 mm × 311 mm (7.65" × 6.30" × 12.24") (L × W × H) |
| Net Weight | 3.1 kg (6.83 lb) |
| Gross Weight | 4.6 kg (10.14 lb) |

Ordering Information

| Type | Model | Description |
|--------------------|------------------------|---|
| Network PTZ Camera | DH-SDT4E425-8P-GB-APV1 | 8+4MP 25x TiOC Network Panoramic PTZ Camera |
| Accessories | PFB305W | Wall Mount Bracket |
| | DC12V/3A | Power Adapter |
| | PFA126 | Mount Adapter |
| | PFA114 | Mount Adapter |
| | PFB300C | Ceiling Mount Bracket |
| | PFB301C | Ceiling Mount Bracket |
| | PFA151 | Corner Mount Bracket |
| | PFA150 | Pole Mount Bracket |
| | PFB303S | Parapet Mount Bracket |
| | PFB301S-E | Plane Mount Bracket |

| Wall Mount | Ceiling Mount 1 | Ceiling Mount 2 |
|--|---|---|
| PFB305W+PFA126 | PFA114+PFB300C | PFA114+PFB301C |
|  |  |  |
| Pole Mount (Vertical) | Corner Mount | Pole Mount (Horizontal) |
| PFB305W+PFA150 | PFB305W+PFA151 | PFA114+PFB300C+PFA150 |
|  |  |  |
| Plane Mount | Parapet Mount | |
| PFB301S-E | PFA114+PFB303S | |
|  |  | |

Accessories

Included:



PFB305W
Wall Mount Bracket

Optional:



DC12V/3A
Power Adapter



PFA126
Mount Adapter



PFA114
Mount Adapter



PFB300C
Ceiling Mount Bracket



PFB301C
Ceiling Mount Bracket



PFA151
Corner Mount Bracket



PFA150
Pole Mount Bracket



PFB303S
Parapet Mount Bracket



PFB301S-E
Plane Mount Bracket

Dimensions (mm[inch])

